

Private Street Signs

Bulletin 19

Division of Building Safety and Inspection for 2018 International Codes

Private Street Sign Requirements

- 1. Post mounted signs shall be constructed of sheet aluminum alloy 6061-T6, 0552-H36 or 5052-H38 with a minimum thickness of .080 inches or 14 gauge.
- 2. The size of the sign shall be a minimum of 24 inches in length and 8-12 inches in height, dependent upon location.
- 3. The minimum letter size on a sign shall be as follows:
 - a. "Private Road" 2" non-arterial intersections, 3" at or along arterials.
 - b. The direction, avenue, or street name 3" non-arterial intersections, 6" at or along arterials.
 - c. The road name 4" non-arterial intersections, 6" at or along arterials.

 See upper detail on page 2
- 4. The color of the sign shall be as follows:
 - a. Type IV white sheeting overlaid with green electro cut film with the street name cut out.

See lower detail on page 2, note #3

5. The sign shall be painted with the street name on both sides.

Signpost Requirements

- 1. Wood posts shall be of untreated western red cedar 4" x 4" nominal dimension. Galvanized post shall be 2" square galvanized (12 gauge) in square heavy wall (7 gauge) galvanized one-piece breakaway anchor.
- 2. The footing for the post shall be a minimum of 27" in depth for galvanized posts and 30" in depth for wood posts.
- 3. The maximum height of the signpost from the finished grade to the bottom of the sign shall not exceed 8 feet. The minimum height shall be not less than 7 feet.

Please Note: Private street name signs shall be maintained by the property owner(s) that have legal access to road or approach and must be installed prior to final inspection.


Protect open sign anchor from filling; PVC sleeve: Only for installation in concrete islands or medians.

Concrete – 12" Min. width (150lbs)

Native

Galvanized Post Detail





Additional sign details are available at the Public Works & Utilities website: http://www.co.pierce.wa.us/index.aspx?nid=1745